

*Estimate N/A-Not Applicable N/R-Not Restricted N/E-Not Established

MATERIAL SAFETY DATA SHEET

| NOIE: BLANK SPACES ARE NOT PERMIT | HED. | IF ANT HEN | 15 NOT APPI | ICABLE, II | | I DE MAKKED | TO INDICATE THAT. | | | | |
|---|--|-----------------------|------------------|-----------------------------------|-------------------------------------|--|-------------------|--|--|--|--|
| IDENTITY | PART NO. | | | | | | | | | | |
| (As shown on Label or package) 14.5 Fluid | ce PLASTI D | IP) | | IF APPLICABLE | | | | | | | |
| SECTION I | | | | | | | | | | | |
| MANUFACTURER'S | EMERGENCY | | | | | | | | | | |
| NAME Plasti Dip International, In | PHONE No. 1-800-424-9300 | | | | | | | | | | |
| ADDRESS (NUMBER, STREET, CITY, STAT | REVISION # | | | | | | | | | | |
| 3920 Pheasant Ridge Drive | | | | | | | | | | | |
| | MANUFACTURER'S PHONE | | | | | | | | | | |
| Blaine, MN 55449 | | | | | | No. FOR INFORMATION 1-763-785-2156 | | | | | |
| | | | | | | DATE MSDS WAS PREPARED December 29, 2011 | | | | | |
| | | | | | | | | | | | |
| SECTION II - HAZARDOUS INGREDIENTS | | RMATION. AI | l Health Hazaı | ds which con | nprise 1% or grea | ater of the comp | osition and all | | | | |
| carcinogens if 0.1% of the composition or grea | | | | | T | | | | | | |
| HAZARDOUS COMPONENTS CHEMICAL | and | % Wt. | | S NO. | OSHA | ACGIH | OTHER LIMITS | | | | |
| IDENTITY AND COMMON NAME (S) | | (OPTIONAL | | | PEL 300 ppm | TLV | RECOMMEND | | | | |
| VM&P Naphtha | | 32-38 | | 64742-89-8 | | 300 ppm | None | | | | |
| Hexane | | 16-19 | | 0-54-3 | 500 ppm | 50 ppm | None | | | | |
| Toluene | | 13-16 | | 8-88-3 | 200 ppm | 50 ppm | None | | | | |
| Methyl Ethyl Ketone | | 3-7 | | 3-93-3 | 200 ppm | 200 ppm | None | | | | |
| Resins | | 25-27 | | N/A | N/A | N/A | None | | | | |
| SECTION III - PHYSICAL / CHEMICAL CH | | | | | , | | | | | | |
| BOILING | SPECIFIC GRAVITY (H ₂ 0 =1) | | | | APPROXIMATE WEIGHT PER GALLON (LBS) | | | | | | |
| POINT 149 - 285°F | 0.79 - 0.83 | | | | 6.60-690 | | | | | | |
| VAPOR PRESSURE | VAPOR DENSITY | | | | EVAPORATION RATE | | | | | | |
| 125 mmHg @ 20°C | (AIR = 1) Heavier than air | | | | (BUTYL ACETATE =1) > 1.0 | | | | | | |
| SOLUBILITY IN WATER | | | 2-75% | | OTHER | | | | | | |
| Insoluble | VOC | LBS./GAL 4. | 8-5.2 | | (IF ANY) None | | | | | | |
| APPEARANCE AND ODOR Various Colors, Honey Like Substance - Characteristic Odor | | | | | | | | | | | |
| | | | e Odor | | | | | | | | |
| SECTION IV-FIRE AND EXPLOSION HAZA | KD D | 1 | | | | | | | | | |
| FLASH POINT -10.0°F | | F | FLAMMABLE LIMITS | | LEL | | UEL | | | | |
| (METHOD USED) TCC | | | 0.9 | 0.9 – 11.5 | | | 11.5 | | | | |
| EXTINGUISHING MEDIA C. I. D. | | | | | | | | | | | |
| MEDIA Carbon Dioxide, Dry Chemical, or Foam | | | | | | | | | | | |
| | SPECIAL FIRE | | | | | | | | | | |
| FIGHTING PROCEDURES Self contained breathing apparatus with a full face piece, operated in pressure demand or other positive pressure mode. | | | | | | | | | | | |
| UNUSUAL FIRE AND EXPLOSION HAZARDS This material is flammable and may be ignited by heat, sparks, flame or static electricity. | | | | | | | | | | | |
| HAZARDOUS PRODUCTS FORMED BY | | | | | | | | | | | |
| FIRE OR THERMAL DECOMPOSITION Carbon Dioxide and/or Carbon Monoxide. | | | | | | | | | | | |
| EXPLOSIVE LIMITS | | | | | | | | | | | |
| (% BY VOLUME IN AIR) 0.9 - 11.5 | | | | | | | | | | | |
| SECTION V - OPTIONAL HAZARD RATINGS IDENTIFICATION | | | | | | | | | | | |
| HAZARD RATING National Fire Protection Association (NFPA) | | | | | | | | | | | |
| 4-EXTREME | | | | A TOWN AND A LOW COMMENT (LILLIA) | | | | | | | |
| 3-HIGH | | | | FIRE 3 REACTIVITY 0. | | | | | | | |
| 2-MODERATE | | <u>-</u> - | | | | | | | | | |
| 1-SLIGHT | | | | | | | | | | | |
| 0-INSIGNIFICANT | | | HEALTH | HEALTH 2 SPECIAL HAZARDS None. | | | | | | | |
| **SEE SECTION IV | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |

This is the "front" when printed in duplex. Page 1 of 2 pages if not duplex.



| I | | | | | | | | | | |
|---|---|--|---|---|--|--|--|--|--|--|
| SECTION VI - REACTIVITY AND STABILITY DATA | | | | | | | | | | |
| STABILITY | UNSTAB | | | TIONS TO A | | | | | | |
| INCOMPATIBILITY (Materials to Avoid) Strong acids, bases, oxidizing agents, selected amines with alkali metals and halogens. | | | | | | | | | | |
| HAZARDOUS DECOMPOSITION OR BY PRODUCTS Carbon Monoxide, Carbon Dioxide | | | | | | | | | | |
| HAZARDOUS | | | OCCUR | CONDIT | CONDITIONS TO AVOID | | | | | |
| POLYMERIZATION | | | L NOT OCCUR X | | None | | | | | |
| SECTION VII - HEALTH HAZARD DATA | | | | | | | | | | |
| ROUTES OF ENTR | Y | INH | ALATION? Yes SKIN? Yes | ING | ESTIC | ON? Yes EYES? Yes | | | | |
| HEALTH | ACUTE | X See Signs and Symptoms of Exposure below. | | | | | | | | |
| HAZARDS | CHRONIC | X Brain and Nervous System Damage (Referred to as solvents or painters syndrome). Drying or Cracking skin. | | | | | | | | |
| CARCINOGENICITY: No | | | | | | | | | | |
| | | | | | | | | | | |
| SIGNS AND | | | | | | | | | | |
| SYMPTOMS OF | • | Headache, Dizziness, Drowsiness, Fatigue, Irregular Heartbeat, Skin and Eye Irritation. | | | | | | | | |
| EXPOSURE | | | | | | | | | | |
| | | | | | | | | | | |
| MEDICAL CONDIT | TIONS GENEI | RALLY | Y AGGRAVATED BY EXPOSURE | Pre-existin | ıg Hear | rt, Liver, Kidney and Lung disorders. | | | | |
| | | | | | | | | | | |
| EMERGENCY AND |) | | tion: Contact Physician or Poison Co | | | | | | | |
| FIRST AID | | | ation: Remove to fresh air. Administ | | | | | | | |
| PROCEDURES | | | Contact: Flush with large amounts of | water. If irr | itation | persists, contact Physician. | | | | |
| | Skin: Wash with soap and water. | | | | | | | | | |
| SECTION VIII - PR | ECAUTIONS | FOR S | SAFE HANDLING AND USE | | | | | | | |
| | | | | | | | | | | |
| STEPS TO BE TAK | TAKEN Wipe up with floor absorbent. Transfer to hood. Prevent run-off to sewers. | | | | | | | | | |
| IN CASE MATERIAL IS Eliminate all sources of ignition. Ventila | | | | e to maintain exposure below PEL's. Use sand or other material to dam | | | | | | |
| RELEASED OR SPILLED or contain spills. If large spill, notify appropriate state and local agencies. | | | | | | | | | | |
| | | | | | | | | | | |
| WASTE DISPOSAL METHODS Dispose of product in accordance with local, county, state and federal regulations. | | | | | | | | | | |
| | | | | | | | | | | |
| PRECAUTIONS TO BE | | | Keep away from sparks, flame and heat sources. Do not store above 120°F and use adequate ventilation. | | | | | | | |
| TAKEN IN HANDLING | | Avoid inhalation of vapors and contact with liquid product. Use good personal hygiene. | | | | | | | | |
| AND STORAGE | | | | | | | | | | |
| | | | | | | | | | | |
| | | | Containers should be disposed of in an environmentally safe manner | | | | | | | |
| PRECAUTIONS in accordance with Governmental Regulations. | | | | | | | | | | |
| SECTION IX - CONTROL MEASURES | | | | | | | | | | |
| RESPIRATORY PROTECTION (SPECIFY TYPE) Depending on the Airbor | | | | tion, | PROTECTIVE GLOVES | | | | | |
| use a Respirator with appropriate NIOSH approved cartridge or supplied air equi | | | ment. | | | | | | | |
| VENTILATION LOCAL EXHAUST Supplemental (if needed) | | | | SPECIAL None | | | | | | |
| MECHANICAL (GENERAL) To maintain exposure be | | | low PEL's | | | | | | | |
| EYE PROTECTION | | L avec | atastian | | OTHER PROTECTIVE CLOTHING OR EQUIPMENT | | | | | |
| Chemical splash goggles or approved eye protection. Impervious Clothing/Boots as needed. WORK HYCHENIC PRACTICES. West theroughly after headling. | | | | | | | | | | |
| WORK HYGIENIC PRACTICES Wash thoroughly after handling. SECTION V. TRANSPORTATION INFORMATION (Options) | | | | | | | | | | |
| SECTION X - TRANSPORTATION INFORMATION (Optional) D.O.T. PROPER SHIPPING NAME Coating Solution (UN 1139) D.O.T. HAZARD CLASS 3, PG II | | | | | | | | | | |
| | | | | D.O.T. HAZARD CLASS 3, PG II | | | | | | |
| IATA PROPER SHIPPING NAME Coating Solution (UN 1139) IATA HAZARD CLASS 3, PG II POT EXCEPTION See DOT 40CFF 173 103 New See in Provision 140 AND DOT 40CFF 171 8 FOR CONSUMER COMMODITY ORM D | | | | | | | | | | |
| DOT EXCEPTION See DOT 49CFR 172.102, New Special Provision 149 AND DOT 49CFR 171.8 FOR CONSUMER COMMODITY, ORM-D | | | | | | | | | | |
| SECTION XI - 313 S | | | | | | | | | | |
| | | | = | | | NG REQUIREMENTS OF SECTION 313 OF THE | | | | |
| | | | AUNITY RIGHT -TO-KNOW ACT | r OF 1986, 4 | 40 CFI | R 372, (see table on page 1 for CAS # and percent by weight). | | | | |
| Hexane, Toluene and | | | NO A CHEMICAL PROMISE TO | HE OF AFE | OFC | AT LEODNITY BO CYTICE CAPICED THE BANK | | | | |
| | | | | HE STATE | OF C | CALIFORNIA TO CAUSE CANCER AND BIRTH | | | | |
| DEFECTS, OR OTHER REPRODUCTIVE HARM. | | | | | | | | | | |

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By: Mark Kenow