



## **MATERIAL SAFETY DATA SHEET**

NOTE: BLANK SPACES ARE NOT PERM	III I ED. IF A	NY ITEMIS N	OI APPLICABLE, THE		BE MAKKED	10 INDICATE THAT.		
IDENTITY		PART NO.						
(As shown on Label or package) F-938		IF APPLICAL	BLE					
SECTION I								
MANUFACTURER'S				EMERGENCY PHONE No.				
NAME Plasti Dip Internation	al, Inc.			1-800-424-930				
ADDRESS (NUMBER, STREET, CITY, ST.	ATE AND ZIP	CODE)		REVISION #				
3920 Pheasant Ridge Drive								
				MANUFACT	URER'S PHON	NE		
Blaine, MN 55449	<b>No. FOR INFORMATION</b> 1-763-785-2156							
		DATE MSDS						
				WAS PREPARED May 13, 2010				
SECTION II - HAZARDOUS INGREDIEN	TS INFORMAT	ΓΙΟΝ. All Hea	alth Hazards which comp	rise 1% or greate	r of the compo	sition and all carcinogens		
if 0.1% of the composition or greater.			•	8	•	3		
HAZARDOUS COMPONENTS CHEMIC	AL and	% Wt.	CAS NO.	OSHA	ACGIH	OTHER LIMITS		
IDENTITY AND COMMON NAME (		OPTIONAL)	31201101	PEL	TLV	RECOMMEND		
Toluene		83-87	108-88-3	200ppm	50ppm	Skin		
Xylene		6-10	1330-20-7	100ppm	100ppm	None		
Ethylbenzene		1-3	100-41-4	100 ppm	100 ppm	None		
					FF			
SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS								
<b>POINT</b> 232 - 279°F	( 2 /			7.23				
VAPOR PRESSURE VAPOR DENSITY				EVAPORATION RATE				
22 mmHg @ 20°C				(BUTYL ACETATE =1) > 1.0				
SOLUBILITY IN WATER	(AIR = 1) Heavier than air % VOLATILE 95%			OTHER				
Insoluble				(IF ANY) None				
APPEARANCE	TOC EDS. G.	0.07		(11 /11/1)	Tione			
AND ODOR Characteristic solvent odor -	clear liquid							
SECTION IV-FIRE AND EXPLOSION HA								
FLASH POINT 45°F	ZAKD DATA	FLAMMAI	DI E I IMITS	LEL	T	JEL		
(METHOD USED) TCC		FLAMMABLE LIMITS		1.0		7.0		
(METHOD USED) TCC EXTINGUISHING				1.0		7.0		
MEDIA Carbon Dioxide, Dry Chem	ical or Foam							
SPECIAL FIRE	near, or roam							
	ned breathing an	maratus with a	full face piece, operated in	pressure demand	or other positive	nressure mode		
UNUSUAL FIRE AND	nea oreanning ap	paratus with a	run race piece, operateu in	pressure demand	or other positive	pressure mode.		
	ial is flammable	and may be jor	nited by heat, sparks, flame	or static electricit	V			
HAZARDOUS PRODUCTS FORMED BY		und may be ign	nica of near, sparies, mane	or state electricity	, .			
FIRE OR THERMAL DECOMPOSITION	Carbon Dioxi	ide and/or Carb	on Monoxide, Hydrogen C	Chloride and organ	ic hydrocarbons			
EXPLOSIVE LIMITS					<u>-</u>	·		
(% BY VOLUME IN AIR) 1.0 – 7.0								
SECTION V - OPTIONAL HAZARD RATI	NGS IDENTIF	ICATION						
HAZARD RATING  National Fire Protection Association (NFPA)								
4-EXTREME	1101101101		)					
3-HIGH			FIRE 3 REACT	TIVITY 0.				
2-MODERATE				<u></u>				
1-SLIGHT								
0-INSIGNIFICANT			HEALTH 2 SPECIAL HAZARDS None.					
**SEE SECTION IV								

This is the "front" when printed in duplex. Page 1 of 2 pages if not duplex.



STABILITY	UNSTAF	BLE STABLE X	CONDITIONS TO	<b>DAVOID</b> Temperatures over 350°F for over 10 minutes.				
INCOMPATIBILITY	Oxidizing Ma							
HAZARDOUS DECOMPOSITION OR BY PRODUCTS Carbon Monoxide, Carbon Dioxide, Hydrogen Chloride, and other organic hydrocarbons.								
HAZARDOUS								
POLYMERIZATION		WILL NOT OCCUR X	0011211101101101	None				
SECTION VII - HEA								
ROUTES OF ENTRY		INHALATION? Yes SKIN? Yes	es INGESTI	ON? Yes EYES? Yes				
HEALTH	ACUTE	X See Signs and Symptoms of Expos		OTT. 103 BIBS. 103				
HAZARDS	CHRONIC	X   See Signs and Symptoms of Exposure below. X						
CARCINOGENICITY: Eth ylbenzene (IARC 2B)								
SIGNS AND	, , ,							
SYMPTOMS OF		Inhalation: Headache, nausea, and irritation of nose, throat and lungs. Skin: Irritation upon repeat or						
EXPOSURE		prolonged contact. Eyes: Slightly irritation to eyes.						
Em opera		protonges commen. 2,000. Onginaj nituaton to 0,000.						
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE None known								
	0110 021121		Trone mio vii					
EMERGENCY AND	EMERGENCY AND Ingestion: Contact Physician or Poison Control Immediately.							
FIRST AID		Inhalation: Remove to fresh air. Admini	•					
PROCEDURES		Eye Contact: Flush with large amounts of		*				
		Skin: Wash with soap and water.	į į					
SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE								
SECTION VIII - I RECRUITORIS I ON SIM E IMMODERIO MAD USE								
STEPS TO BE TAKE	STEPS TO BE TAKEN  Wipe up with floor absorbent. Transfer to hood. Prevent run-off to sewers.							
IN CASE MATERIAL		Eliminate all sources of ignition. Ventilate to maintain exposure below PEL's. Use sand or other material						
RELEASED OR SPILLED		to dam or contain spills. If large spill, notify appropriate state and local agencies.						
RELEASED OR STILL	ZEED	to dain of contain spins. If large spin, no	any appropriate state	e and rocar agencies.				
WASTE DISPOSAL I	METHODS	Dispose of product in accordance with loc	cal, county, state and	l federal regulations.				
		The second secon	<u>, , , , , , , , , , , , , , , , , , , </u>					
PRECAUTIONS TO	BE	Keep away from sparks, flame and heat s	ources. Store in co	ol ventilated area.				
TAKEN IN HANDLI	NG	Avoid contact with eyes. Keep container closed. Use with adequate ventilation. Avoid inhalation of vapors						
AND STORAGE		and personal contact with liquid product.						
			3	7.6 · · · · · · · · · · · · · · · · · · ·				
OTHER		Keep container closed when not in use.	All containers shoul	d be disposed in an environmentally safe manner				
PRECAUTIONS								
SECTION IX - CONTROL MEASURES								
RESPIRATORY PROTECTION (SPECIFY TYPE) Depending on the Airborne co			e concentration.	PROTECTIVE GLOVES				
use a Respirator with appropriate NIOSH approved cartridge or supplied air equip				Rubber gloves				
		AUST Supplemental (if needed)		SPECIAL None				
MECHANICAL (GENERAL) To maintain exposu		L (GENERAL) To maintain exposure be	low PEL's.	OTHER None				
EYE PROTECTION				OTHER PROTECTIVE CLOTHING OR EQUIPMENT				
Chemical splash goggles or approved eye protection.				Chemical Apron/Eye bath/Safety shower				
WORK HYGIENIC PRACTICES Wash thoroughly after handling.								
SECTION X - TRANSPORTATION INFORMATION (Optional)								
DOT PROPER SHIPPING NAME Coating Solution DOT HAZARD CLASS 3								
DOT UN NUMBER UN 1139		DOT PACKING GROUP II						
IATA PROPER SHIPPING NAME Coating Solution		IATA HAZARD CLASS 3						
IATA UN NUMBER UN 1139			IATA PACKING GROUP II					
SECTION XI - 313 SUPPLIER NOTIFICATION								
THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT -TO-KNOW ACT OF 1986, 40 CFR 372, (see table on page 1 for CAS # and percent by weight). Toluene, Xylene, and Ethylbenzene								
	WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.							

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By: Michael N Hindin	epared By:	Michael N Hindin	
-------------------------------	------------	------------------	--