

## MATERIAL SAFETY DATA SHEET

<b>NOTE: BLANK SPACES ARE NOT PERMITTED. IF ANY ITEM IS NOT APPLICABLE, THE SPACE MUST BE MARKED TO INDICATE THAT.</b>					
<b>IDENTITY</b> (As shown on Label or package) <b>RUBBER DIP F698, F819, F820</b>				<b>PART NO.</b> <b>IF APPLICABLE</b>	
<b>SECTION I</b>					
<b>MANUFACTURER'S NAME</b> Plasti Dip International, Inc.				<b>EMERGENCY PHONE No.</b> 1-800-424-9300	
<b>ADDRESS (NUMBER, STREET, CITY, STATE AND ZIP CODE)</b> 3920 Pheasant Ridge Drive				<b>REVISION #</b>	
Blaine, MN 55449				<b>MANUFACTURER'S PHONE No. FOR INFORMATION</b> 1-763-785-2156	
				<b>DATE MSDS WAS PREPARED</b> January 3, 2012	
<b>SECTION II - HAZARDOUS INGREDIENTS INFORMATION. All Health Hazards which comprise 1% or greater of the composition and all carcinogens if 0.1% of the composition or greater.</b>					
<b>HAZARDOUS COMPONENTS CHEMICAL and IDENTITY AND COMMON NAME (S)</b>	<b>% Wt. (OPTIONAL)</b>	<b>CAS NO.</b>	<b>OSHA PEL</b>	<b>ACGIH TLV</b>	<b>OTHER LIMITS RECOMMEND</b>
VM&P Naphtha	32-38	64742-89-8	300 ppm	300 ppm	None
Hexane	16-19	110-54-3	500 ppm	50 ppm	None
Toluene	13-16	108-88-3	200 ppm	50 ppm	None
Methyl Ethyl Ketone	3-7	78-93-3	200 ppm	200 ppm	None
Resins	25-27	N/A	N/A	N/A	None
<b>SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS</b>					
<b>BOILING POINT</b> 149 - 285°F	<b>SPECIFIC GRAVITY (H<sub>2</sub>O =1)</b> 0.79 - 0.83		<b>APPROXIMATE WEIGHT PER GALLON (LBS)</b> 6.60-690		
<b>VAPOR PRESSURE</b> 125 mmHg @ 20°C	<b>VAPOR DENSITY (AIR = 1)</b> Heavier than air		<b>EVAPORATION RATE (BUTYL ACETATE =1)</b> > 1.0		
<b>SOLUBILITY IN WATER</b> Insoluble	<b>% VOLATILE</b> 72-75%	<b>VOC LBS./GAL</b> 4.8-5.2	<b>OTHER (IF ANY)</b> None		
<b>APPEARANCE AND ODOR</b> Various Colors, Honey Like Substance - Characteristic Odor					
<b>SECTION IV-FIRE AND EXPLOSION HAZARD DATA</b>					
<b>FLASH POINT (METHOD USED)</b> -10.0°F TCC	<b>FLAMMABLE LIMITS</b> 0.9 - 11.5		<b>LEL</b> 0.9	<b>UEL</b> 11.5	
<b>EXTINGUISHING MEDIA</b> Carbon Dioxide, Dry Chemical, or Foam					
<b>SPECIAL FIRE FIGHTING PROCEDURES</b> Self contained breathing apparatus with a full face piece, operated in pressure demand or other positive pressure mode.					
<b>UNUSUAL FIRE AND EXPLOSION HAZARDS</b> This material is flammable and may be ignited by heat, sparks, flame or static electricity.					
<b>HAZARDOUS PRODUCTS FORMED BY FIRE OR THERMAL DECOMPOSITION</b> Carbon Dioxide and/or Carbon Monoxide.					
<b>EXPLOSIVE LIMITS (% BY VOLUME IN AIR)</b> 0.9 - 11.5					
<b>SECTION V - OPTIONAL HAZARD RATINGS IDENTIFICATION</b>					
<b>HAZARD RATING</b> 4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT 0-INSIGNIFICANT **SEE SECTION IV			<b>National Fire Protection Association (NFPA)</b>  <b>FIRE</b> <u>  3  </u> <b>REACTIVITY</b> <u>  0  </u> .  <b>HEALTH</b> <u>  2  </u> <b>SPECIAL HAZARDS</b> <u>  None  </u> .		

This is the "front" when printed in duplex. Page 1 of 2 pages if not duplex.

SECTION VI - REACTIVITY AND STABILITY DATA			
STABILITY	UNSTABLE	STABLE X	CONDITIONS TO AVOID None
INCOMPATIBILITY (Materials to Avoid) Strong acids, bases, oxidizing agents, selected amines with alkali metals and halogens.			
HAZARDOUS DECOMPOSITION OR BY PRODUCTS Carbon Monoxide, Carbon Dioxide			
HAZARDOUS POLYMERIZATION	MAY OCCUR	WILL NOT OCCUR X	CONDITIONS TO AVOID None
SECTION VII - HEALTH HAZARD DATA			
ROUTES OF ENTRY	INHALATION? Yes	SKIN? Yes	INGESTION? Yes EYES? Yes
HEALTH HAZARDS	ACUTE X	CHRONIC X	See Signs and Symptoms of Exposure below. Brain and Nervous System Damage (Referred to as solvents or painters syndrome). Drying or Cracking skin.
CARCINOGENICITY: No			
SIGN AND SYMPTOMS OF EXPOSURE			
Headache, Dizziness, Drowsiness, Fatigue, Irregular Heartbeat, Skin and Eye Irritation.			
Target Organs: CNS, CVS, PNS, Liver, Kidneys, Lungs, Respiratory System, Skin.			
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE Pre-existing Heart, Liver, Kidney and Lung disorders.			
EMERGENCY AND FIRST AID PROCEDURES			
Ingestion: Contact Physician or Poison Control Immediately.			
Inhalation: Remove to fresh air. Administer Oxygen or Artificial Respiration if Necessary.			
Eye Contact: Flush with large amounts of water. If irritation persists, contact Physician.			
Skin: Wash with soap and water.			
SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE			
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED			
Wipe up with floor absorbent. Transfer to hood. Prevent run-off to sewers.			
Eliminate all sources of ignition. Ventilate to maintain exposure below PEL's. Use sand or other material to dam or contain spills. If large spill, notify appropriate state and local agencies.			
WASTE DISPOSAL METHODS Dispose of product in accordance with local, county, state and federal regulations.			
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE			
Keep away from sparks, flame and heat sources. Do not store above 120°F and use adequate ventilation.			
Avoid inhalation of vapors and contact with liquid product. Use good personal hygiene.			
OTHER PRECAUTIONS			
Keep Container Closed When Not In Use. Containers should be disposed of in an environmentally safe manner in accordance with Governmental Regulations.			
SECTION IX - CONTROL MEASURES			
RESPIRATORY PROTECTION (SPECIFY TYPE) Depending on the Airborne concentration, use a Respirator with appropriate NIOSH approved cartridge or supplied air equipment.		PROTECTIVE GLOVES Impervious	
VENTILATION	LOCAL EXHAUST Supplemental (if needed)	SPECIAL None	
	MECHANICAL (GENERAL) To maintain exposure below PEL's	OTHER None	
EYE PROTECTION Chemical splash goggles or approved eye protection.		OTHER PROTECTIVE CLOTHING OR EQUIPMENT Impervious Clothing/Boots as needed.	
WORK HYGIENIC PRACTICES Wash thoroughly after handling.			
SECTION X - TRANSPORTATION INFORMATION (Optional)			
D.O.T. PROPER SHIPPING NAME Coating Solution (UN 1139)		D.O.T. HAZARD CLASS 3, PG II	
IATA PROPER SHIPPING NAME Coating Solution (UN 1139)		IATA HAZARD CLASS 3, PG II	
DOT EXCEPTION See DOT 49CFR 172.102, New Special Provision 149 AND DOT 49CFR 171.8 FOR CONSUMER COMMODITY, ORM-D			
SECTION XI - 313 SUPPLIER NOTIFICATION			
THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT -TO-KNOW ACT OF 1986, 40 CFR 372, (see table on page 1 for CAS # and percent by weight). Hexane, Toluene and Methyl Ethyl Ketone			
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.			

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By: Mark Kenow

THE INFORMATION PROVIDED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS OBTAINED FROM ITS USE. SINCE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND THE VENDORS CONTROL AND SINCE SUBSEQUENT DATA MAY SUGGEST MODIFICATION OF THE INFORMATION, VENDOR ASSUMES NO RESPONSIBILITY FOR THE RESULTS OF ITS USE.