

*Estimated N/A-Not Applicable N/R-Not Restricted N/E-Not Established

MATERIAL SAFETY DATA SHEET

NOTE: BLANK SPACES ARE NOT PE	RMITTED.	IF ANY ITEM IS	S NOT APPLICABLE, TH	<u>IE SPACE MUST</u>	BE MARKED	TO INDICATE THAT.
IDENTITY				PART NO.		
(As shown on Label or package) THINNER (F-740)				IF APPLICA	BLE	
SECTION I						
MANUFACTURER'S				EMERGENC	Y PHONE No.	
NAME Plasti Dip International, Inc.			USA only: 1-800-424-9300 INT'L: 703-527-3887			
ADDRESS (NUMBER, STREET, CITY, STATE AND ZIP CODE)				REVISION #		
3920 Pheasant Ridge Drive		,				
			MANUFACTURER'S PHONE			
Blaine, MN 55449			No. FOR INFORMATION 1-763-785-2156			
				DATE MSDS		
				WAS PREPARED March 30, 2012		
SECTION II - HAZARDOUS INGREDII	ENTS INFO	RMATION. All I	Health Hazards which com	prise 1% or great	ter of the compo	sition and all
carcinogens if 0.1% of the composition or						
HAZARDOUS COMPONENTS CHEM		% Wt.	CAS NO.	OSHA	ACGIH	OTHER LIMITS
IDENTITY AND COMMON NAM		(OPTIONAL)		PEL	TLV	RECOMMEND
Toluene	(-)	65	108-88-3	200 ppm	50 ppm	None
VM&P Naphtha		35	64742-89-8	300 ppm	300 ppm	None
					FF	
SECTION III - PHYSICAL / CHEMICA	L CHARAC	TERISTICS	•		<u>I</u>	I.
BOILING		GRAVITY (H ₂ 0	-1)	APPROVIM	TE WEIGHT	DED CALLON
POINT 232 - 285°F	SIECIFIC	0.81 –	,	ATTROXIVIA	6.90	ER GALLON
VAPOR PRESSURE	VAPOR DENSITY EVAPORATION RATE					
22 mmHg @ 20°C	(AIR = 1) Heavier than air (BUTYL ACETATE =1) > 1.0			1.0		
SOLUBILITY IN WATER	% VOLATILE 100 OTHER					
Insoluble	VOC LBS./GAL 6.90			(IF ANY) None		
APPEARANCE				(== === ,=)		
AND ODOR Clear Liquid, Characteris	stic Solvent C	Odor.				
SECTION IV-FIRE AND EXPLOSION I						
FLASH POINT 45°F			LAMMABLE LIMITS	LEL		UEL
(METHOD USED) TCC		Emministration Emminis		.9	7.0	
EXTINGUISHING					.,	7.10
MEDIA Carbon Dioxide, Dry C	hemical or F	oam				
SPECIAL						
FIRE FIGHTING PROCEDURES Self	contained bre	eathing apparatus v	with a full face piece, operate	ed in pressure dem	and or other posi	itive pressure mode.
UNUSUAL FIRE AND		8 11				
EXPLOSION HAZARDS This material	is flammable	and may be ignited	d by heat, sparks, flame or st	atic electricity.		
HAZARDOUS PRODUCTS FORMED B		, ,		·		
FIRE OR THERMAL DECOMPOSITION	N Carbon	Dioxide and/or Ca	arbon Monoxide			
EXPLOSIVE LIMITS						
(% BY VOLUME IN AIR) 0.9 – 7.0						
SECTION V - OPTIONAL HAZARD RA	TINGS IDE	NTIFICATION				
HAZARD RATING			National Fire Protection	on Association (N	FPA)	
4-EXTREME				`	,	
3-HIGH			FIRE 3 REACT	IVITY <u>0</u> .		
2-MODERATE						
1-SLIGHT						
0-INSIGNIFICANT			HEALTH 2 S	PECIAL HAZAR	None None	<u>.</u>
**SEE SECTION IV						

This is the "front" when printed in duplex. Page 1 of 2 pages if not duplex.



SECTION VI - REACTIVITY AN	ND STABILITY DATA				
STABILITY UNSTA	BLE STABLE X	CONDITIONS TO	AVOID None		
INCOMPATIBILITY (Materials to Avoid) Strong acids, bases, oxidizing agents, selected amines and with alkali metals and halogens.					
HAZARDOUS DECOMPOSITIO	N OR BY PRODUCTS Carbon Monoxid				
HAZARDOUS	MAY OCCUR	CONDITIONS TO	AVOID		
POLYMERIZATION	WILL NOT OCCUR X		None		
SECTION VII - HEALTH HAZA	RD DATA				
ROUTES OF ENTRY INHALATION? Yes SKIN? Yes INGESTION? Yes EYES? Yes					
HEALTH ACUTE	X See Signs and Symptoms of Expo				
HAZARDS CHRONIC	X Brain and Nervous System Dama	ige (Referred to as sol	lvents or painters syndrome). Drying or Cracking skin.		
CARCINOGENICITY: No					
SIGNS AND					
SYMPTOMS OF	Headache, Dizziness, Drowsiness, Fatig	ue, Irregular Heartbe	at, Skin and Eye Irritation.		
EXPOSURE	Target Organs: CNS, CVS, PNS, Liver,	, Kidneys, Lungs, Res	spiratory System, Skin.		
MEDICAL CONDITIONS CENT	DALLY ACCDANATED BY EVECT	DE Des estates Han	4 Time Widen and Lone discussion		
MEDICAL CONDITIONS GENE	RALLY AGGRAVATED BY EXPOSU	RE Pre-existing Hea	rt, Liver, Kidney and Lung disorders.		
EMERGENCY AND	Ingestion: Contact Physician or Poison	Control Immediately			
FIRST AID	Inhalation: Remove to fresh air. Admir				
PROCEDURES	Eye Contact: Flush with large amounts				
ROCEDORES	Skin: Wash with soap and water.	or water. In influence	persists, contact i hysician.		
SECTION VIII - PRECAUTIONS	S FOR SAFE HANDLING AND USE				
BEGIN VIII TIEBERGINE					
STEPS TO BE TAKEN	Wipe up with floor absorbent. Transfer	to hood. Prevent run	n-off to sewers.		
IN CASE MATERIAL IS	Eliminate all sources of ignition. Ventilate to maintain exposure below PEL's. Use sand or other material				
RELEASED OR SPILLED	to dam or contain spills. If large spill, n				
WASTE DISPOSAL METHODS	Dispose of product in accordance with loc	al, county, state and	federal regulations.		
PRECAUTIONS TO BE			e above 120°F. Store this product with adequate		
TAKEN IN HANDLING		ventilation. Avoid inhalation of vapors and personal contact with liquid product. Use good personal hygiene			
AND STORAGE	practices.				
OTHER Keep Container Closed When Not In Use. All containers should be disposed of in an environmentally safe					
PRECAUTIONS manner accordance with governmental regulations.					
SECTION IX - CONTROL MEAS					
	(SPECIFY TYPE) Depending on the Airbo		PROTECTIVE GLOVES		
	DSH approved cartridge or supplied air equipment. Impervious Gloves AUST Supplemental (if needed) SPECIAL None				
	TILATION LOCAL EXHAUST Supplemental (if needed) SPECIAL None MECHANICAL (GENERAL) To maintain exposure below PEL's OTHER None				
EYE PROTECTION OTHER PROTECTIVE CLOTHING OR EQUIPMENT					
			Chemcial Apron/Eye bath/Safety Shower		
WORK HYGIENIC PRACTICES			Chemical Informative dualibrately bliother		
SECTION X - TRANSPORTATION					
DOT PROPER SHIPPING NAME	(1 /	DOT HAZARD	CLASS 3		
DOT UN NUMBER UN1263 DOT PACKING GROUP II					
IATA PROPER SHIPPING NAME Paint Related Material IATA HAZARD CLASS 3					
IATA UN NUMBER UN1263 IATA PACKING GROUP II					
SECTION XI - 313 SUPPLIER NOTIFICATION					
		ECT TO REPORTI	NG REQUIREMENTS OF SECTION 313 OF THE		
			R 372, (see table on page 1 for CAS # and percent by weight).		
Toluene		,			
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH					

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

D 1 D	Morte Vanore	
Prepared By:	Mark Kenow	