



*Estimate N/A-Not Applicable N/R-Not Restricted N/E-Not Established

MATERIAL SAFETY DATA SHEET

NOTE: BLANK SPACES ARE NOT	PERMITTI	ED. IF ANY ITEM	IS NOT APPLICABLE	, THE SPACE M	UST BE MARK	ED TO INDICATE THAT.			
IDENTITY		PART NO.							
(As shown on Label or package) VLP	(F-631)	IF APPLICABLE							
SECTION I									
MANUFACTURER'S		EMERGENC	EMERGENCY PHONE No.						
NAME Plasti Dip Interna		USA only: 1-8	USA only: 1-800-424-9300 INT'L: 703-527-3887						
ADDRESS (NUMBER, STREET, CIT	Y, STATE	REVISION #	REVISION # 0003						
3920 Pheasant Ridge Drive									
		MANUFACTURER'S PHONE							
Blaine, MN 55449				No. FOR INFORMATION 1-763-785-2156					
		DATE MSDS							
		WAS PREPARED March 25, 2010							
SECTION II - HAZARDOUS INGREI			ll Health Hazards which	comprise 1% or g	reater of the co	mposition and all			
carcinogens if 0.1% of the composition			CACNO	OCITA	ACCITI	OTHER I DATE			
HAZARDOUS COMPONENTS CHE and IDENTITY AND COMMON NA		% Wt. (OPTIONAL)	CAS NO.	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMEND			
Tetrahydrofuran	IVIE (5)	60.3	109-99-9	200 ppm	200 ppm	None			
Methyl Ethyl Ketone		18.9	78-93-3	200 ppm	200 ppm	None			
Cyclohexanone		2.4	108-94-1	50 ppm	25 ppm	None			
Cyclonexanone		2.4	100-94-1	эо ррш	23 ppiii	None			
SECTION III - PHYSICAL / CHEMIC	CAL CHAR	ACTERISTICS	1	I	I .	I			
BOILING	SPECIFIC GRAVITY (H ₂ 0 =1) APPROXIMATE WEIGHT PER GALLON (LBS)								
POINT 151 – 175°F	SI LCII I	0.90 -		7.65					
VAPOR PRESSURE	VAPOR DENSITY			EVAPORATION RATE					
143 mmHg @ 20°C	(AIR = 1) Heavier than air			(BUTYL ACETATE =1) >1.0					
SOLUBILITY IN WATER	% VOLA	TILE 81.6		OTHER					
insoluble	VOC LBS	S./GAL 6.2		(IF ANY)					
APPEARANCE									
AND ODOR Clear liquid, strong solv	ent odor								
SECTION IV-FIRE AND EXPLOSION	N HAZARI) DATA							
FLASH POINT 6.0°F	FLAMMABLE LIMITS		LEL		UEL				
(METHOD USED) TCC		1.3		11.8					
EXTINGUISHING									
MEDIA Carbon Dioxide, Dry	Chemical,	or Foam							
SPECIAL FIRE			0.11.0						
FIGHTING PROCEDURES Self con	tained breat	hing apparatus with	a full face piece, operated	in pressure deman	d or other positiv	e pressure mode.			
UNUSUAL FIRE AND									
EXPLOSION HAZARDS This material is flammable and may be ignited by heat, sparks, flame or static electricity.									
HAZARDOUS PRODUCTS FORMED BY									
FIRE OR THERMAL DECOMPOSITION Carbon Dioxide and/or Carbon Monoxide									
EXPLOSIVE LIMITS (% BY VOLUME IN AIR) 1.3 – 11.8									
SECTION V - OPTIONAL HAZARD	RATINCS:	IDENTIFICATIO	N						
HAZARD RATING	KATINGS.	IDENTIFICATIO		on Association (N	EDA)				
4-EXTREME			National Fire Protection Association (NFPA)						
3-HIGH			FIRE 3 REACTIVITY 0.						
2-MODERATE			TIME 5 KEACH	, <u>, , , , , , , , , , , , , , , , , , </u>					
1-SLIGHT									
0-INSIGNIFICANT	HEALTH 2 SPECIAL HAZARDS None .								
**SEE SECTION IV									
			1						

This is the "front" when printed in duplex. Page 1 of 2 pages if not duplex.



SECTION VI - REACTIVITY AND STABILITY DATA										
STABILITY UNSTABLE STABLE X										
INCOMPATIBILITY (Materials to Avoid) Strong acids, bases, oxidizing agents, selected amines with alkali metals and halogens.										
HAZARDOUS DECOMPOSITION OR BY PRODUCTS										
HAZARDOUS MAY OCCUR					CONDITIONS TO AVOID					
POLYMERIZA	TION	WIL	L NOT OCCUR X	Ma	by be ignited by heat, sparks, flame or static electricity					
SECTION VII -	HEALTH H	AZAR	D DATA							
ROUTES OF E	NTRY	INH	ALATION? YES	SKIN? YES	INGESTION?	YES EYES? YES				
HEALTH	ACUTE	X								
HAZARDS	CHRONIC	X								
CARCINOGEN	ICITY: No									
SIGNS AND										
SYMPTOMS O	F	Head	eadache, Dizziness, Drowsiness, Fatigue, Irregular Heartbeat, Skin and Eye Irritation.							
EXPOSURE										
MEDICAL CO.	UDITIONIC C	ENED	ATTACA CODATA TED	DAY EXPOSEIT						
MEDICAL CO	NDITIONS G	ENEK	ALLY AGGRAVATED	BY EXPOSUE	<u>CE</u>					
EMEDGENCY	AND	T.,	-ti Ctt Dhi-i	. D.: C	-1 T 4! -41					
EMERGENCY FIRST AID	AND	Ingestion: Contact Physician or Poison Control Immediatley.								
PROCEDURES	!		Inhalation: Remove to fresh air. Administer Oxygen or Artificial Respiration if Necessary.							
			Eye Contact: Flush with large amounts of water. If irritation persists, contact Physician. Skin: Wash with soap and water.							
SECTION VIII	- PRECAUTI		OR SAFE HANDLING							
SECTION VIII	- I KECAUTI	ONSI	OK SAFE HANDLING	AND USE						
STEPS TO BE	TAKEN	Wine	un with floor absorbent	Transfer to hoo	od Prevent run-off to	o sewers				
						be below PEL's. Use sand or other material to dam or contain				
RELEASED OF			s. If large spill, notify app			of the first state of the first				
			3-1 , , , , , , , ,		8					
WASTE DISPO	SAL METHO	DDS D	rispose of product in accord	dance with loca	al, county, state and f	federal regulations.				
PRECAUTIONS TO BE Avoid eye contact with ey			d eye contact with eyes. K	eep container	ep container closed. Use with adequate ventilation. Keep away from sparks, flame and heat					
TAKEN IN HA	NDLING	Sour	Sources and store in a cool area. Avoid inhalation of vapors and personal contact with liquid product.							
AND STORAG	E	Use good personal hygiene practices.								
OTHER										
PRECAUTION			Governmental Regulations	3.						
SECTION IX -						1				
RESPIRATORY PROTECTION (SPECIFY TYPE) Depending on the Airbor						PROTECTIVE GLOVES				
VENTILATION		ppropriate NIOSH approved cartridge or supplied air o			пршеш.	ment. Impervious Gloves SPECIAL None				
VENTILATION	VENTILATION LOCAL EXHAUST Supplemental (if needed) MECHANICAL (GENERAL) To maintain exposure be				alaw DEL la					
EYE PROTECTION			ani exposure o	CIOW FEL S	OTHER PROTECTIVE CLOTHING OR EQUIPMENT					
Chemical splash goggles, or approved eye protection.				Chemcial Apron/Eye bath/Safety Shower						
WORK HYGIENIC PRACTICES Wash thoroughly after handling.										
SECTION X - TRANSPORTATION INFORMATION										
DOT PROPER SHIPPING NAME Coating Solution DOT HAZARD CLASS 3										
DOT UN NUMBER UN1139				DOT PACKING GROUP II						
IATA PROPER SHIPPING NAME Coating Solution				IATA HAZARD CLASS 3						
IATA UN NUM			Coating Solution		IATA PACKING GROUP II					
SECTION XI - 313 SUPPLIER NOTIFICATION										
				CALS SUBJE	CT TO REPORTIN	NG REQUIREMENTS OF SECTION 313 OF THE				
						R 372, (see table on page 1 for CAS # and percent by weight).				
Methyl Ethyl Ke		~				, commercial fragments and promisely mediantly				
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH										
DEFECTS OF OTHER DEPRODUCTIVE HARM										

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.